

Two pieces Fixing Ties with Fir Tree,with Disc for Round hold



Two pieces Fixing Ties with Fir Tree,with Disc for Round hold							Heating Resistant		High Temperature		Operating Temperature: -40°C~+105°C			
Product code	Max bundle diameter		Size(mm)				Ø C(mm)	Panel Thickness (mm)		Hole Ø (mm)	Applicable screw	Min. loop Tensile Strength N(kgf)	Packing pcs/pack	
	Ø (mm)	L	w	T	A	B		Min.	Max					
QX30														
QX30RFT5-HSB	31	150.0	3.5	1.2	13.2	6.9	16	0.70	3	4.5-5.0	M6	135(13.77)	100	
QX30RFT6-HSB	31	150.0	3.5	1.2	13.8	7.5	16	0.80	3	6.4-7.1	M8	135(13.78)	100	
QX50														
QX50RFT5-HSB	45	200.0	4.6	1.2	13.2	6.9	16	0.70	3	4.5-5.0	M6	225(22.94)	100	
QX50RFT6-HSB	45	200.0	4.6	1.2	13.8	7.5	16	0.75	3	6.4-7.1	M8	225(22.94)	100	
QX50RFT7-HSB	45	200.0	4.6	1.2	18.9	12.7	15.8	0.80	7	6.5-7.0	M8	225(22.94)	100	
QX50RFT8-HSB	45	200.0	4.6	1.2	17.4	11.5	16	0.80	6	7.7-8.0	Screw holes	225(22.94)	100	
QX50RFT10-HSB	45	200.0	4.6	1.2	18.5	12.2	18.2	0.80	5	9.7-10.0	M12	225(22.94)	100	
QX50LFT7-HSB	100	390	4.6	1.5	18.9	12.7	15.8	0.8	7	6.5-7.0	M8	225(22.94)	50	
QX50LFT8-HSB	100	390	4.6	1.5	17.4	11.5	16	0.8	6	7.7-8.0	Screw holes	225(22.94)	50	
QX50LFT10-HSB	100	390	4.6	1.5	18.5	12.2	18.2	0.8	5	9.7-10.0	M12	225(22.94)	50	



Heating and Weather Resistant				High Temperature and outdoor				High Temperature and outdoor: -40°C~+105°C					
Product code	Max bundle diameter		Size(mm)				Ø C(mm)	Panel Thickness (mm)		Hole Ø (mm)	Applicable screw	Min. loop Tensile Strength N(kgf)	Packing pcs/pack
	Ø (mm)	L	w	T	A	B		Min.	Max				
QX18													
QX18RFT3-HSW	20	100.0	2.5	1.1	10.2	4.0	13	1.5	3	M3	M3	80(8.16)	100
QX18RFT4-HSW	20	100.0	2.5	1.1	11.8	5.6	13	1	3	3.3-4.0	M4	80(8.16)	100
QX30													
QX30RFT4-HSW	31	150.0	3.5	1.2	11.8	5.6	13	1	3	3.3-4.0	M4	135(13.77)	100
QX120													
QX120RFT11-HSW	95	380.0	7.6	1.8	16.5	8.2	16	0.8	4.5	6.5-7.0	M8	535(54.46)	50